



## Perfil "U"

Os Perfis "U" são produzidos em chapa de aço carbono SAE 1006/1010, em barras de 3000 mm.

Chapa				Dimensões mm	
MSG	mm	Kg/m	Kg/3m	a	b
18	1,20	0,532	1,596	20	20
16	1,50	0,635	1,905	20	20
14	2,00	0,820	2,460	20	20
18	1,20	0,665	1,995	25	25
16	1,50	0,815	2,445	25	25
18	1,20	0,750	2,250	28	28
16	1,50	0,920	2,760	28	28
18	1,20	0,805	2,415	30	30
16	1,50	0,990	2,970	30	30
18	1,20	0,945	2,835	35	35
16	1,50	1,170	3,510	35	35
18	1,20	0,999	2,997	37	37
16	1,50	1,237	3,711	37	37
18	1,20	1,090	3,270	40	40
16	1,50	1,345	4,035	40	40

Chapa				Dimensões mm	
MSG	mm	Kg/m	Kg/3m	a	b
18	1,20	0,335	1,005	20	10
16	1,50	0,400	1,200	20	10
18	1,20	0,430	1,290	20	15
16	1,50	0,520	1,560	20	15
18	1,20	0,520	1,560	30	15
16	1,50	0,640	1,920	30	15
18	1,20	0,615	1,845	30	20
16	1,50	0,755	2,265	30	20
18	1,20	0,570	1,710	35	15
16	1,50	0,695	2,085	35	15
18	1,20	0,615	1,845	40	15
16	1,50	0,755	2,265	40	15
18	1,20	0,923	2,769	45	30
16	1,50	1,133	3,399	45	30

Chapa				Dimensões mm	
MSG	mm	Kg/m	Kg/3m	a	b
18	1,20	0,710	2,130	40	20
16	1,50	0,875	2,625	40	20
18	1,20	0,760	2,280	45	20
16	1,50	0,930	2,790	45	20
18	1,20	0,805	2,415	50	20
16	1,50	0,990	2,970	50	20
18	1,20	0,995	2,985	80	15
16	1,50	1,230	3,690	80	15
18	1,20	1,180	3,540	100	15
16	1,50	1,465	4,395	100	15

Chapa				Dimensões mm	
MSG	mm	Kg/m	Kg/3m	a	b
18	1,20	1,370	4,110	120	15
16	1,50	1,700	5,100	120	15
18	1,20	1,465	4,395	120	15
16	1,50	1,815	5,445	120	15
18	1,20	1,655	4,965	150	15
16	1,50	2,055	6,165	150	15
18	1,20	1,845	5,535	170	15
16	1,50	2,290	6,870	170	15
18	1,20	2,125	6,375	200	15
16	1,50	2,640	7,920	200	15
13	2,25	1,786	5,358	30	40
14	2,00	1,604	4,812	30	40
18	1,50	1,002	3,006	35	25
16	1,20	0,802	2,406	35	25