



Perfil Cadeirinha Aberta

Os Perfis "Cadeirinha Aberta" são produzidos em chapa de aço carbono SAE 1006/1010, em barras de 3000 mm.

Chapa				Dimensões mm	
MSG	mm	Kg/m	Kg/3m	a	b
18	1,20	0,786	2,358	30	25
18	1,20	1,295	3,885	55	25
18	1,20	0,889	2,667	35	25
18	1,20	1,192	3,576	50	25
18	1,20	0,993	2,979	40	25
18	1,20	1,092	3,276	45	25
18	1,20	1,700	5,100	75	25
18	1,20	1,497	4,491	65	25
18	1,20	1,380	4,140	60	25
18	1,20	2,212	6,636	100	25
18	1,20	1,908	5,724	85	25
18	1,20	0,848	2,544	30	30
18	1,20	1,352	4,056	55	30
18	1,20	0,949	2,847	35	30
18	1,20	1,252	3,756	50	30
18	1,20	1,050	3,150	50	30
18	1,20	1,151	3,453	45	30
18	1,20	1,554	4,662	65	30
18	1,20	1,454	4,362	60	30
18	1,20	2,261	6,783	100	30

Chapa				Dimensões mm	
MSG	mm	Kg/m	Kg/3m	a	b
16	1,50	0,950	2,850	30	100
16	1,50	1,565	4,695	55	100
16	1,50	1,075	3,225	35	100
16	1,50	1,440	4,320	50	100
16	1,50	1,200	3,600	40	100
16	1,50	1,320	3,960	45	100
16	1,50	2,055	6,165	75	100
16	1,50	1,810	5,430	65	100
16	1,50	1,668	5,004	60	100
16	1,50	2,673	8,019	100	100
16	1,50	2,306	6,918	85	100
16	1,50	1,025	3,075	30	30
16	1,50	1,635	4,905	55	30
16	1,50	1,147	3,441	35	30
16	1,50	1,513	4,539	50	30
16	1,50	1,269	3,807	40	30
16	1,50	1,390	4,170	45	30
16	1,50	1,879	5,637	65	30
16	1,50	1,750	5,250	60	30
16	1,50	2,734	8,202	100	30