



Perfil Cadeirinha Fechada

Os Perfis "Cadeirinha Fechada" são produzidos em chapa de aço carbono SAE 1006/1010, em barras de 3000 mm.

Chapa				Dimensões mm	
MSG	mm	Kg/m	Kg/3m	a	b
18	1,20	1,001	3,003	30	25
18	1,20	1,506	4,518	55	25
18	1,20	1,100	3,300	35	25
18	1,20	1,406	4,218	50	25
18	1,20	1,204	3,612	40	25
18	1,20	1,303	3,909	45	25
18	1,20	1,708	5,124	65	25
18	1,20	1,605	4,815	60	25
18	1,20	2,403	7,209	100	25
18	1,20	2,100	6,300	85	25
18	1,20	0,888	2,664	30	30
18	1,20	1,090	3,270	30	30
18	1,20	1,625	4,875	55	30
18	1,20	1,191	3,573	35	30
18	1,20	1,494	4,482	50	30
18	1,20	1,291	3,873	40	30
18	1,20	1,392	4,176	45	30
18	1,20	1,796	5,388	65	30
18	1,20	1,695	5,085	60	30
18	1,20	2,502	7,506	100	30
18	1,20	2,200	6,600	85	30

Chapa				Dimensões mm	
MSG	mm	Kg/m	Kg/3m	a	b
16	1,50	1,210	3,630	30	25
16	1,50	1,820	5,460	55	25
16	1,50	1,330	3,990	35	25
16	1,50	1,700	5,100	50	25
16	1,50	1,455	4,365	40	25
16	1,50	1,575	4,725	45	25
16	1,50	2,065	6,195	65	25
16	1,50	1,940	5,820	60	25
16	1,50	2,905	8,715	100	25
16	1,50	2,538	7,614	85	25
16	1,50	1,074	3,222	30	30
16	1,50	1,318	3,954	30	30
16	1,50	1,965	5,895	55	30
16	1,50	1,440	4,320	35	30
16	1,50	1,805	5,415	50	30
16	1,50	1,562	4,686	40	30
16	1,50	1,684	5,052	45	30
16	1,50	2,172	6,516	65	30
16	1,50	2,050	6,150	60	30
16	1,50	3,027	9,081	100	30
16	1,50	2,660	7,980	85	30